



DUO-SAFETY LADDER - MARINE DIVISION

MF - Overside Ladders

Just as the name implies, these ladders are used on large vessels for over the side work. For that reason, they are equipped with folding hooks at the top and offset brackets at the top and bottom of the ladder. Because aluminum is impervious to moisture, they have proved long lasting and inexpensive for this type of work. To maintain light weight, this model is made in the Channel Rail Construction.

Series MF

Channel Rail Construction
500 lb Duty Rated
12" Rung Centers



10' MF

6' MF

Only length without small standoff bracket

SPECIFICATIONS


SERIES MF

Size	Length	Width	Rail Size	Weight
6'	6' 2.25"	18.5"	2.75"	16 lbs
7'	7' 2.25"	18.5"	2.75"	18 lbs
8'	8' 2.25"	18.5"	2.75"	20 lbs
9'	9' 2.25"	18.5"	2.75"	22 lbs
10'	10' 2.25"	18.5"	2.75"	24 lbs
11'	11' 2.25"	18.5"	2.75"	29 lbs
12'	12' 2.25"	18.5"	2.75"	33 lbs
14'	14' 2.25"	18.5"	2.75"	36 lbs
16'	16' 2.25"	18.5"	2.75"	40 lbs
18'	18' 2.25"	18.5"	2.75"	49 lbs
20'	20' 2.625"	18.5"	3.25"	55 lbs
24'	24' 2.625"	22.5"	3.25"	63 lbs
25'	25' 3.125"	22.5"	3.75"	66 lbs
30'	30' 3.5"	22.5"	3.75"	75 lbs

Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.



Roof Hook Info:
Arch Opening - 8"
Hook Diameter - 0.75"

Standoff Measurements/height:
Small Top Standoff - 2.75" from rail
Large Bottom Standoff - 6.75" from rail