



# DUO-SAFETY LADDER - MARINE DIVISION

## MHDR - Double Rung Boarding Ladders

MHDR Boarding Ladders are used by ore carriers and cargo vessels to take on and unload passengers and crew members. Exposed to moisture and hard usage, this Duo-Safety Ladder proved more durable - more economical. Because these ladders are required in lengths of 20' and longer, and because greater rigidity is essential, they are fashioned in Tubular Rail Construction. Handrails are applied for additional safety.

### Series MHDR

**Tubular Rail Construction**

**500 lb Duty Rated**

**12" Rung Centers**

**Lengths 25' and below available without handrails**

#### SPECIFICATIONS

#### SERIES MHDR

Size	Overall Length	Width	Rail Size	Rail Size w/Handrail	Weight
16'	16' 5.5"	24"	6"	12"	78 lbs
18'	18' 5.5"	24"	6"	12"	86 lbs
20'	20' 5.5"	24"	6"	12"	94 lbs
22'	22' 5.5"	24"	6"	12"	102 lbs
24'	24' 5.5"	24"	6"	12"	109 lbs
25'	25' 5.5"	24"	6"	12"	113 lbs
26'	26' 5.5"	24"	6"	12"	120 lbs
28'	28' 5.5"	24"	6"	12"	126 lbs
30'	30' 5.5"	24"	6"	12"	135 lbs
32'	32' 5.5"	24"	6"	12"	145 lbs
34'	34' 5.5"	24"	6"	12"	155 lbs
35'	35' 5.5"	24"	6"	12"	163 lbs
36'	36' 5.5"	24"	6"	12"	170 lbs
38'	38' 5.5"	24"	6"	12"	180 lbs
40'	40' 5.5"	24"	6"	12"	190 lbs
42'	42' 5.5"	24"	6"	12"	225 lbs
45'	45' 5.5"	24"	6"	12"	260 lbs
46'	46' 5.5"	24"	6"	12"	268 lbs
48'	48' 5.5"	24"	6"	12"	280 lbs
50'	50' 5.5"	24"	6"	12"	295 lbs

Pictured with Safety Shoes - Spike Feet Std



Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Spike feet as Standard

Rubber safety shoes optional for hard surface use.

DUO-SAFETY LADDER - Marine Division 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377 Fax 920-231-2460 mail@duosafety.com www.duosafety.com/marine