



DUO-SAFETY LADDER CORPORATION

Folding Roof Ladder

Equipped with directional folding roof hooks, the Folding Roof Ladder was designed to save space when stored on your fire truck unit. This ladder easily folds for side mounting on a standard engine, yet opens and locks into a long roof ladder for use.

****Please note: this ladder is NOT designed for use as an A-frame style ladder, refer to our 35B or 300A models.**

Series 1275-FR

3 3/4" Channel Rail
750 lb Duty Rated



Shown in a slightly open/closing position to demonstrate how it folds up for storage **NOT intended to be used in this manner.**

SPECIFICATIONS

SERIES 1275-FR

Lengths	Extended Length	Closed Length	Width	Banking Thickness	Weight
8' - 16'	20' 4.75"	8' 3"	*19"	7.625"	65#
10' - 20'	20' 4.75"	10' 3"	*19"	7.625"	72#
12' - 24'	24' 4.75"	12' 3"	*19"	7.625"	80#
14' - 28'	28' 4.75"	14' 3"	*19"	7.625"	86#
15' - 30'	30' 4.75"	15' 3"	*19"	7.625"	97#

* Overall width including bolt heads on hinge brackets = 20.25"

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com