



DUO-SAFETY LADDER CORPORATION

Combination Step and Extension Ladders

The 300 Series Combination Ladder is ideal for indoor fire fighting. In attics and other confined spaces, this sturdy, ruggedly constructed ladder can be quickly and easily changed from an 8' step to a 13' extension. Extra strong rails and rungs are typical of the heavy duty construction that means extra safety and service provided by this practical, versatile ladder.

Series 300-A

**2 3/4" Channel Rail
750 lb Duty Rated**



SPECIFICATIONS

SERIES 300-A Aluminum

Size	Closed Length	Height as Step Ladder	Length Extended	Width	Banking Thickness	Weight
6' - 9'	6' 2"	5' 6"	9'	*23.25"	**5.68"	34#
8' - 13'	8' 2.25"	7' 6"	13'	*23.25"	**5.68"	42#
10' - 15'	9' 10.875"	9' 6"	15'	*23.25"	**5.68"	47#

* Overall width including bolt heads on hinge brackets = 23.75"

**Overall banking height including rivet heads and spreader bar = 6.43"

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com