



DUO-SAFETY LADDER CORPORATION

Aluminum Truss Fire Ladders

The 500-C Series ladders represent great strength and extraordinary safety. All this is incorporated into the tubular rail construction of this ladder. Available in all standard sizes - see specifications below.

Series 500-C Series 525-C

750 lb Duty Rated

SPECIFICATIONS

SERIES 500-C 2-SECTION

Size	Closed Length	Width	Width Over Poles	Banking Thickness	Weight
14'	9' .75"	24"		7"	74#
16'	10' .75"	24"		7"	75#
18'	11' .75"	24"		7"	76#
20'	12' .75"	24"		7"	78#
24'	14' .625"	24"		7"	90#
28'	16' .625"	24"		8"	112#
30'	18' .75"	24"		8"	131#
35'	20'	24"		8"	153#
40'	23' .75"	24"	*26"	8"	210#
45'	26' .75"	24"	26"	9"	255#
50'	28' .75"	24"	26"	9"	279#

SERIES 525-C 3-SECTION

Size	Closed Length	Width	Width Over Poles	Banking Thickness	Weight
28'	13' .75"	26"		10.25"	140#
30'	14' .75"	26"		10.25"	164#
35'	15' 4"	26"		10.25"	179#
40'	17' 7.75"	26"	*28.5"	10.25"	245#
45'	19' .75"	26"	28.5"	11.25"	265#
50'	21' 2.75"	26"	28.5"	11.25"	297#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

*Staypoles are optional on 40ft length
Weight without poles deduct approx. 35 lbs each

All Extension ladders 40' and over are equipped with 1/2" manila rope as standard

Prong feet as Standard
Rubber safety shoes optional for hard surface use.

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com