



# DUO-SAFETY LADDER CORPORATION

## Aluminum Roof Ladders

Famous Duo-Safety Rail Construction provides the advantage of extra strength without cumbersome weight. Ideal for pumper use - these outstanding ladders have been proven and approved for many years by fire companies everywhere. Installed with standard 3/4" hooks or heavy duty 7/8" hooks for an additional fee.

### Series 775-A Series 875-A Series 1275-A

Channel Rail Construction  
750 lb Duty Rated



#### SPECIFICATIONS

##### SERIES 775-A ROOF

Size	Length	Width	Rail Size	Weight
10'	10' 2.25"	19"	2.75"	22#
12'	12' 2.25"	19"	2.75"	24#
14'	14' 2.25"	19"	2.75"	28#

##### SERIES 875-A ROOF

Size	Length	Width	Rail Size	Weight
16'	16' 2.5"	19"	3.25"	39#
18'	18' 2.5"	19"	3.25"	44#
20'	20' 2.5"	19"	3.25"	48#

##### SERIES 1275-A ROOF

Size	Length	Width	Rail Size	Weight
25'	25' 3"	19"	3.75"	64#
30'	30' 3"	19"	3.75"	72#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

**Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.**

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com