



DUO-SAFETY LADDER - MARINE DIVISION

MH - Single Rung Boarding Ladders

MH Boarding Ladders are used by ore carriers and cargo vessels to take on and unload passengers and crew members. Exposed to moisture and hard usage, this Duo-Safety Ladder proved more durable - more economical. Because these ladders are required in lengths of 20' and longer, and because greater rigidity is essential, they are fashioned in Tubular Rail Construction. Handrails are applied for additional safety.

Series MH

Tubular Rail Construction

500 lb Duty Rated

12" Rung Centers

Lengths 25' and below available without handrails



MH pictured with Safety Shoes - Spike Feet are standard

SPECIFICATIONS

SERIES MH

Size	Overall Length	Width	Rail Size	Rail Size w/Handrail	Weight
16'	16' 5.5"	24"	6"	12"	80 lbs
18'	18' 5.5"	24"	6"	12"	85 lbs
20'	20' 5.5"	24"	6"	12"	91 lbs
22'	22' 5.5"	24"	6"	12"	98 lbs
24'	24' 5.5"	24"	6"	12"	105 lbs
25'	25' 5.5"	24"	6"	12"	109 lbs
26'	26' 5.5"	24"	6"	12"	114 lbs
28'	28' 5.5"	24"	6"	12"	120 lbs
30'	30' 5.5"	24"	6"	12"	128 lbs
32'	32' 5.5"	24"	6"	12"	135 lbs
34'	34' 5.5"	24"	6"	12"	140 lbs
35'	35' 5.5"	24"	6"	12"	145 lbs
36'	36' 5.5"	24"	6"	12"	150 lbs
38'	38' 5.5"	24"	6"	12"	163 lbs
40'	40' 5.5"	24"	6"	12"	171 lbs

Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Spike feet as Standard

Rubber safety shoes optional for hard surface use.

DUO-SAFETY LADDER - Marine Division 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377 Fax 920-231-2460 mail@duosafety.com www.duosafety.com/marine