



DUO-SAFETY LADDER CORPORATION

Combination Jackknife "A" & Single Ladders

An unusually versatile ladder with countless uses for both indoor and outdoor work. This combination ladder serves as a rugged single ladder - or can be easily converted into a sturdy "A" Type ladder with a double climbing side. Strong, heavy gauge steel locking device makes changeover easy and fast. Equipped with famous Duo-Safety Ladder shoes for extra safety.

Series 35-FGB

- 3 1/4" Channel Rail
- 750 lb Duty Rated
- Special self-extinguishing resin - will not support flame
- Special high temperature resins for heat resistance
- Special ultra-violet screen for fade resistance
- Safety yellow color for better visibility in smoke
- Rubber Safety Shoes Standard



SPECIFICATIONS

SERIES 35-FGB Fiberglass

Size	Closed Length	Height as (A) Type	Length as single	Width	Banking Thickness	Weight
4' - 8'	4' 2.75"	3' 11.5"	8' 3.25"	*19.25"	**8"	42#
6' - 12'	6' 2.75"	5' 11.5"	12' 3.25"	*19.25"	**8"	46#
7' - 14'	7' 2.75"	6' 11.5"	14' 3.25"	*19.25"	**8"	49#
8' - 16'	8' 2.75"	6' 11.5"	16' 3.25"	*19.25"	**8"	53#

* Overall width including safety shoes = 19.75"

**Banking height includes safety shoes tilted in open position

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com