



DUO-SAFETY LADDER CORPORATION

Aluminum Truss Fire Ladders

The tubular construction of Duo-Safety's 500-C Series incorporates the inherent strength of a rectangle, a channel and an "I" beam combined to provide the ultimate in strength and safety. Construction features include: double parallel fins; double set of truss plates; ribbed, extruded rungs, electrically welded to outside of truss plates; and aluminum rivets.

Series 575-C Roof

Series 550-C Wall

750 lb Duty Rated

SPECIFICATIONS

SERIES 575-C Roof

Size	Length	Width	Rail Size	Weight
10'	10' .5"	19.75"	4.5"	39#
12'	12' .5"	19.75"	4.5"	43#
14'	14' .5"	19.75"	4.5"	50#
16'	16' .5"	19.75"	4.5"	55#
18'	18' .5"	19.75"	4.5"	57#
20'	20' .5"	19.75"	4.5"	63#
25'	25' .5"	19.75"	4.5"	80#
30'	30' .5"	19.75"	5.5"	100#

SERIES 550-C Wall

Size	Length	Width	Rail Size	Weight
10'	10' .5"	22.5"	4.5"	31#
12'	12' .5"	22.5"	4.5"	37#
14'	14' .5"	22.5"	4.5"	44#
16'	16' .5"	22.5"	4.5"	48#
18'	18' .5"	22.5"	4.5"	55#
20'	20' .5"	22.5"	4.5"	59#
22'	22' .5"	22.5"	4.5"	67#
24'	24' .5"	22.5"	4.5"	74#
25'	25' .5"	22.5"	4.5"	77#
26'	26' .5"	22.5"	5.5"	81#
28'	28' .5"	22.5"	5.5"	88#
30'	30' .5"	22.5"	5.5"	96#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.



Model 575C



Model 550C

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com