



DUO-SAFETY LADDER CORPORATION

Solid Beam Aluminum Ladders

Originally produced for the Forestry Departments for use on their brush pumps. This ladder was designed for a maximum closed length to fit in a restricted space. Due to the compact design, this ladder does not have a cable pulley to help extend the fly section. In order to extend the ladder, you must first extend the fly section by hand and use the rope and pulley to fully extend the ladder.

Series 912

3 1/4" Channel Rail
750 lb Duty Rated



SPECIFICATIONS

SERIES 912-86 3-SECTION

Size	Closed Length	Width	Banking Thickness	Weight
16'	86"	24"	8.125"	65#

SERIES 912-100 3-SECTION

Size	Closed Length	Width	Banking Thickness	Weight
20'	100"	24"	8.125"	80#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Note: Due to compact size - you must manually extend fly/top section by hand and use the rope & pulley to fully extend the ladder

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com