



DUO-SAFETY LADDER CORPORATION

Aluminum Double End Roof Ladders

Famous Duo-Safety Rail Construction provides the advantage of extra strength without cumbersome weight. This ladder was designed for firefighters so that no matter what end of the ladder is on top at the roof peak, there are hooks available. Installed with standard 3/4" hooks or heavy duty 7/8" hooks for an additional fee.

Series 775-DR

Series 875-DR

Channel Rail Construction
750 lb Duty Rated



SPECIFICATIONS

SERIES 775-DR DOUBLE END ROOF

Size	Length	Width	Rail Size	Weight
10'	10' 1.625"	19"	2.75"	29#
12'	12' 1.625"	19"	2.75"	33#
14'	14' 1.625"	19"	2.75"	35#

SERIES 875-DR DOUBLE END ROOF

Size	Length	Width	Rail Size	Weight
16'	16' 2.125"	19"	3.25"	49#
18'	18' 2.125"	19"	3.25"	53#
20'	20' 2.125"	19"	3.25"	56#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

MFG Note: We **do not** recommend retro fitting older ladders for double hooks

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

Prong feet on both ends as Standard
Rubber safety shoes optional for hard surface use.